

Safety Task Card

STCGE 08



What other precautions should be taken?



Clean up any spillages immediately

Use of trolleys and sack trucks

Unit Managers – use page overleaf to list any hazards and control measures specific to your site which are not listed below

Safe System of Work

- 1. Visually check trolleys and sack trucks before use. Make sure wheels are clean of debris and free running.
- 2. Trolleys and sack trucks should be loaded so that the way ahead can be seen and they must not be overloaded to prevent the risk of collapse.
- 3. Load heavier items below lighter items.
- 4. Ensure the load is stable and use a restraint if necessary.
- 5. Hot food and liquids must be securely contained on trolleys to prevent spillage, especially where they are taken over uneven or sloping surfaces.
- 6. Always make sure the pathway is clear.
- 7. Loaded trolleys should be moved by pushing rather than by pulling whenever possible.
- 8. If possible, routes with uneven surfaces, ramps or steps should be avoided.
- 9. Two people should move trolleys with heavy loads, over uneven surfaces, over slopes and kerbs, through heavy or narrow doorways and passageways or through crowded areas.
- 10. Trolleys must not be carried up or down steps or stairs.
- 11. Clean up spillages as they occur and use wet floor warning signs when appropriate.

If you have any concerns, stop and speak with your line manager before proceeding.



